CAMERA HEAD DUAL CAMERA Ø 5,5 mm flexibel - 1 m

for RC3 Inspection camera

Item no.: 21001





DATA	
ITEM NO.:	21001
WEIGHT NET	0,05 kg
DIMENSION	L 1040 mm x B 13 mm x H 7 mm
DIAMETER	5,5 mm
LENGTH	1 m
INTEGRATED LIGHTING	6 x LED (dimmable)
IMAGE RESOLUTION	1920 x 1080 und 1280 x 720 pixels
ANGLE OF VIEW	70 °
FOCUS DISTANCE	Front camera 15 – 50 mm Side camera 20 – 80 mm
PROTECTION CLASS	IP67
EAN-CODE	9120045477979

ADVANTAGES

- Flexible gooseneck for individual viewing angle adjustment
- Suitable for RC3 inspection camera
- Protection class IP67
- Viewing angle 70 degrees
- 5.5 mm dual camera
 (1 x front and 1 x side camera
- 6 integrated LEDs (dimmable)
- For areas that are difficult to access
- High image quality

DESCRIPTION

The dual camera (1 x front camera and 2 x side camera) with a diameter of $5.5 \, \text{mm}$ is a practical accessory for the RC3 inspection camera. The front camera and autofocus provide clear images in the range from 15 mm to 50 mm - ideal for precise close-ups. The 1 metre semi-rigid cable combines flexibility and stability to easily reach even narrow areas.

It is compatible with the RC3 inspection camera and comes with handy accessories (hook, magnet and lens cap) to make it easier to inspect hard-to-reach areas.

Image resolution: Selectable between 1920×1080 pixels and 1280×720 pixels for different applications.

LED illumination: Six integrated LEDs (dimmable) ensure optimum lighting conditions and a clear view, even in dark areas.

Waterproof: Ideal for use in damp environments. The camera is waterproof to IPA7

Versatile: Perfect for inspecting cavity walls, plants, machines, motors and ventilation systems as well as hard-to-reach cavities, narrow angles, shafts, ducts and small penetrations.

Ideal for short distances: The flexible gooseneck allows precise work in the tightest of spaces

Scope of supply: 1 x dual camera \varnothing 5.5 mm, length 1 meter, 1 x hook,

1 x magnet, 1 x lens protection cap

