

Fiberglass rods Ø 3 mm – Set

2 x 1 m, RTG Ø 6 mm thread, stainless steel

Item No.: **21045**

RUNPOSTICKS

Click here Video


[Click here
Productinformation](#)
DATA

ITEM NO.	21045
DIAMETER	Ø 3 mm
WEIGHT	0,033 kg
DIMENSIONS	L 1050 mm x W 7 mm x H 7 mm
THREAD	RTG Ø 6 mm
EAN-CODE	9120045478303

DESCRIPTION

The fibreglass rod (Ø 3 mm, length 1 m) is mainly used in combination with RUNPOSTICKS as an additional guide probe. The standard RTG Ø 6 mm thread allows for a wide variety of combinations. All accessories can be screwed on without the need for an additional adapter. It can also be easily combined with the RC3, which expands its range of applications.

Optimal area of application: suspended ceilings, cable ducts, cavity walls, rewiring of unguided cables, underfloor ducts, feed-throughs, etc.

Scope of supply: 2 x Fiberglass rod Ø 3 mm - Length: 1 m

ADVANTAGES

- Guide probe for narrow bends
- Bending radius 55 mm
- Standard RTG Ø 6 mm thread

INFORMATION**Compatible with:****RUNPOSTICKS**

17-parts - Item No. 10016

19-parts - Item No. 10020

35-parts - Item No. 10173


[Click here
Productinformation](#)